Full Leather Welding Jacket

Leather Clothing Range





Made from premium-quality 100% Grade-A split leather, the ESAB leather welding jacket provides the ultimate protection from welding hazards.

The front is reinforced in order to withstand mechanical and thermal stress.

- Durable Grade-A slit leather
- Metal snap enclosures
- Double-stitched internal pocket
- Reinforced Kevlar® stitching throughout
- Hook and loop collar fastener
- Adjustable cuffs with metal snaps

Visit **esab.com** for more information.

Process

- Oxy-Fuel Cutting
- Plasma Cutting
- Grinding
- Welding, GMAW (MIG/MAG)
- Welding, GTAW (TIG)
- Welding, PAW -Plasma Arc Welding
- Welding, SMAW/MMA (Stick)

Full Leather Welding Jacket

Specifications			
Operating Temperature	-10 to +40 °C (+14 to +104 °F)		
Weight	3.2 kg (7 lbs)		
Country Of Origin	India		
Certifications C € CA	CE, EN ISO 11611:2015, Class 2A1; UKCA 2019 S1696 Schedule 35 Reg. 38		

Approvals – EN ISO 11611:2015, Class 2A1



Intended Use:

Class 2- recommended for manual welding techniques with heavy formation of spatters and drops e.g MMA welding (with basic or cellulose-covered electrode), MAG welding (CO2 or mixed gases), MIG welding (with high current), self-shielded flux cored arc welding, plasma cutting, gouging, oxygen cutting, thermal spraying for operation of machines e.g. in confined spaces, at overhead welding / cutting or in constrained positions. This clothing is intended to protect against flames, molten metal, spatter, radiant heat and short term, accidental electrical contact.

Ordering Information		
Leather Welding Jacket, M	0700500414	
Leather Welding Jacket, L	0700500415	
Leather Welding Jacket, XL	0700500416	
Leather Welding Jacket, 2XL	0700500417	

Sizing				
Chest	Sleeve Length	Torso Length	Size	
112 cm (44 in.)	81 cm (32 in.)	76 cm (30 in.)	М	
122 cm (48 in.)	84 cm (33 in.)	76 cm (30 in.)	L	
132 cm (52 in.)	86 cm (34 in.)	76 cm (30 in.)	XL	
142 cm (56 in.)	89 cm (35 in.)	76 cm (30 in.)	2XL	





ESAB / esab.com







